

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/042183 A1

(51) International Patent Classification⁷: E21B 10/26, 7/28

(21) International Application Number:
PCT/SE2003/001485

(22) International Filing Date:
24 September 2003 (24.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0203286-0 7 November 2002 (07.11.2002) SE

(71) Applicant (for all designated States except US): ATLAS
COPCO SECOROC AB [SE/SE]; Box 521, S-737 25
Fagersta (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VIRTANEN, Stefan
[SE/SE]; Solbacksallén 14A, S-738 34 Norberg (SE).

(74) Agents: KARLSTRÖM, Lennart et al.; Noréns Patent-
byrå AB, Box 10198, S-100 55 Stockholm (SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A REAMER ASSEMBLY



(57) Abstract: The present invention relates to a reamer assembly for widening a drilled pilot hole or for widening a hole that has been widened in a first step in a down-the-hole drilling operation, wherein the reamer assembly includes a shank (14) for attachment of the reamer to the end of a down-the-hole hammer drill and a conical drill bit or crown (15). The conical bit (15) of the reamer is divided into at least three segments (18) which are terminated with a transverse end surface (21) that directly connects said conical segments and at least three of said segments (18) include drill buttons (16) that are disposed equidistantly from the centre axis of the drill bit (15).